

# Granville FS-MB 0W/40

1 Litre, 5 Litre, 20 Litre & 199 Litre

## PRODUCT DESCRIPTION

FS-MB 0W/40 is a fully synthetic high performing engine oil produced using the very latest in additive technology in combination with selected base oils. FS-MB 0W/40 is suitable for use in petrol and diesel engine both turbo charged and naturally aspirated including fuel injected and multivalve engine types.

## RECOMMENDED FOR USE BY GRANVILLE FOR THE FOLLOWING MANUFACTURER'S SPECIFICATIONS

ACEA: A3/B4

API: SN/CF

MB: 226.5 & 229.5

Porsche: A40

Renault: RN0700 & RN0710

VW: 502.00 & 505.00

Ford: WSS-M2C937-A



\* Image for illustrative purposes only.

SIZE	PART NO	BARCODE
1 Litre	1174	5020618011743
5 Litre	1175	5020618011750
20 Litre	1176	5020618011767
199 Litre	1177	5020618011774

## PRODUCT BENEFITS

Excellent component protection

Good High & low heat control

## PRODUCT USAGE

Use where this specification and viscosity is required.

## DIRECTIONS FOR USE

As recommended by the engine manufacturer.

## STORAGE INSTRUCTIONS

Store upright and sealed in a cool dry place and out of the reach of children.



# Granville FS-MB 0W/40

1 Litre, 5 Litre, 20 Litre & 199 Litre

## SHELF LIFE

5 years from date of manufacture.

**Appearance** : Clear Amber liquid

**Odour** : Characteristic

**Solubility** : Insoluble in Water

Test	Method	Unit	Min.	Max.	Typical
Kinematic Viscosity at 100°C	ASTM D445	mm <sup>2</sup> /s	12.5	<16.3	13.81
Cold Cranking Viscosity	ASTM D4684	mPa.s		6200	
Total Base Number	ASTM D2896	mg KOH/g	10		10.6
Pour Point	ASTM D97	°C		-27	
HTHS Viscosity	ASTM D4683	mPa.s	3.5		
NOACK Volatility	ASTM D5800	%		<10	
Kinematic Viscosity at 40°C	ASTM D445	mm <sup>2</sup> /s			79.32
Density	ASTM D792	@ 15°C			0.845

## SAFETY PRECAUTIONS

Please see our latest EC Safety Data Sheets for details.

## TRANSPORT CLASSIFICATION

Please see our latest EC Safety Data Sheets for details.

